



6008—90

(497—89)

199/0e—8 eg

• " * 0Z

—

6008—90

Metallic manganese and nitrated manganese
Specifications

(CT 497—89)

08 3400

01.07.91

01.07.96

-

,

-

1.

1.1.

»

-

1.2.

1.2.1.

,

.

. 1.

		, %						
998 9 97	-	99,8 99,7	0,04 0,06	—	0,003 0,005	0,03	—	
965 95	- -	96,5 95,0	0,20	0,8 1,8	0,05 0,07	0,05 0,05		
92 6	- -	92,0		—	0,005		6,0	
87 6 \$9 4 91 2	- - -	87,0 89,0 91,0	0,20 0,20 0,20	1,8 1,8 1,8	0,07 0,07 0,07	0,05 0,05 0,05	6,0 4,0 2,0	

1.2.2.

:

0,6% 965;
1,3%,

0,13% 95.

1.2.3.

998 997

()

965, 2x2 95 —

5% ;

15

15 3%

10X10 92 6 —

10% ;

15

87 6, 5x5 89 4, 91 2 —

10% ;

15 .

10

1.2.4.

20%

,

-

965 95.

1.2.5.

1.2.5.1.

12.1.007.

1.2.5.2.

1.2.5.3.

()
0₂—0,3 / 3

12.1.005.

1.2.5.4.

12.1.007

1.2.5.5.

6-

1.2.5.6.

()
90 / 3 —
1000 / 3 —

240° —

620° —

(t .)

12.1.044.

1.3.

26590

965

95

.2

2.

2.1.

()

* ()

2

	/ 8'			- / 3'	1 ;	-
		- / 3'	- / 3'			
* >	0,3	0.01	0 001	0,1	1503	3
-						2
O ₂						
-						
O ₂	0,05					1
-						

1.

. . , . . , . .

2.

17.12.90 3150

3.

— 1996 .
— 5 .

4.

6008—82

5.

497—89

6.

-

-

--	--

<p>12 1 005—88 12 1 007—76 12 1 044—89 166 8 1—71 16698 4—71 16698 5—71 IOCT 16698 13—84 22310-84 1 36590—85 26999—86 10 27041—86 27069—86 28473-90</p>	<p> 12 5 3 1 2 5 1; 1 * 2 5 4 1 2 5 6 3 2 3 2 3 2 3 2 2 4, 3 3 1 3, 4 2 2, 3 2 3 2 3 2</p>
---	---

6000 . 03 0191 » nfew 91 0,5 0,5 .- 0,39 - 20 .

« » « » , 123557, , , 6' 4 ,, 3